


INTRODUCTION




Type **KSD50** Series Rectangular Attenuators are used for ducted systems or medium to large items of plant, to provide a high level of attenuation, whilst allowing passage of air to or from the equipment being treated.

Whilst all **KSD50** Series attenuators are selected to suit particular criteria, in general these are used to provide a better level of attenuation at low to medium frequencies due to the thicker, 250mm, splitter configuration.

The **KSD50** Series attenuators are very efficient at providing Plant Noise Attenuation, as well as being suitable for larger duct cross sectional areas.

All attenuators are designed to suit your individual project, and our Team of Sales Engineers can assist with the design of the attenuation package for the optimum product selection.



DESIGN AND MANUFACTURE

The **KSD50** Series Rectangular Attenuators are designed and fabricated to suit particular projects to take into account the specific sound reduction requirements with regard to both Octave and Broad Band noise, regenerated noise and airflow characteristics, such as the effect on other equipment and pressure drop.

The attenuators are fabricated in line with DW144 and can be varied to suit high pressure or industrial grade systems, as well as bespoke applications.

CONABEARE ACOUSTICS

PERFORMANCE DATA

Type KSD5010 - 300mm Module

| Length (mm) | Insertion (dB) at Octave Band Centre Frequencies (Hz) | | | | | | | | 'K' (Face) |
|-------------|---|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | |
| 600 | 8 | 12 | 23 | 33 | 43 | 45 | 30 | 22 | 33.17 |
| 900 | 10 | 16 | 28 | 40 | 53 | 51 | 39 | 27 | 36.19 |
| 1200 | 11 | 20 | 33 | 47 | 55 | 55 | 47 | 33 | 39.21 |
| 1500 | 13 | 25 | 38 | 54 | 55 | 55 | 55 | 39 | 42.23 |
| 1800 | 14 | 29 | 43 | 55 | 55 | 55 | 55 | 45 | 45.26 |
| 2100 | 16 | 33 | 48 | 55 | 55 | 55 | 55 | 51 | 48.28 |
| 2400 | 18 | 38 | 53 | 55 | 55 | 55 | 55 | 55 | 51.30 |

Type KSD5015 - 325mm Module

| Length (mm) | Insertion (dB) at Octave Band Centre Frequencies (Hz) | | | | | | | | 'K' (Face) |
|-------------|---|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | |
| 600 | 7 | 11 | 20 | 29 | 38 | 37 | 26 | 20 | 14.55 |
| 900 | 9 | 14 | 25 | 35 | 48 | 47 | 33 | 24 | 15.93 |
| 1200 | 10 | 18 | 30 | 42 | 55 | 55 | 40 | 28 | 17.31 |
| 1500 | 12 | 21 | 34 | 48 | 55 | 55 | 48 | 33 | 18.68 |
| 1800 | 13 | 25 | 39 | 55 | 55 | 55 | 55 | 37 | 20.06 |
| 2100 | 15 | 28 | 44 | 55 | 55 | 55 | 55 | 41 | 21.44 |
| 2400 | 16 | 32 | 49 | 55 | 55 | 55 | 55 | 46 | 22.82 |

Type KSD5020 - 350mm Module

| Length (mm) | Insertion (dB) at Octave Band Centre Frequencies (Hz) | | | | | | | | 'K' (Face) |
|-------------|---|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | |
| 600 | 7 | 10 | 18 | 26 | 33 | 32 | 22 | 17 | 7.95 |
| 900 | 8 | 13 | 22 | 33 | 40 | 39 | 28 | 20 | 8.79 |
| 1200 | 9 | 16 | 27 | 39 | 48 | 47 | 35 | 24 | 9.63 |
| 1500 | 11 | 19 | 31 | 46 | 55 | 55 | 41 | 27 | 10.47 |
| 1800 | 12 | 22 | 36 | 52 | 55 | 55 | 47 | 30 | 11.31 |
| 2100 | 14 | 25 | 40 | 55 | 55 | 55 | 54 | 34 | 12.15 |
| 2400 | 15 | 29 | 45 | 55 | 55 | 55 | 55 | 37 | 12.99 |

Type KSD5025 - 375mm Module

| Length (mm) | Insertion (dB) at Octave Band Centre Frequencies (Hz) | | | | | | | | 'K' (Face) |
|-------------|---|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | |
| 600 | 6 | 9 | 16 | 24 | 29 | 27 | 20 | 16 | 4.82 |
| 900 | 7 | 12 | 20 | 30 | 36 | 33 | 24 | 19 | 5.41 |
| 1200 | 9 | 14 | 24 | 36 | 42 | 39 | 28 | 21 | 6.00 |
| 1500 | 10 | 17 | 29 | 43 | 49 | 45 | 32 | 24 | 6.59 |
| 1800 | 11 | 20 | 33 | 49 | 55 | 50 | 36 | 26 | 7.19 |
| 2100 | 13 | 22 | 37 | 55 | 55 | 55 | 40 | 29 | 7.78 |
| 2400 | 14 | 25 | 41 | 55 | 55 | 55 | 45 | 32 | 8.37 |

Type KSD5030 - 400mm Module

| Length (mm) | Insertion (dB) at Octave Band Centre Frequencies (Hz) | | | | | | | | 'K' (Face) |
|-------------|---|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | |
| 600 | 4 | 6 | 11 | 16 | 21 | 19 | 15 | 14 | 3.06 |
| 900 | 4 | 8 | 15 | 22 | 28 | 24 | 18 | 15 | 3.51 |
| 1200 | 5 | 10 | 19 | 29 | 35 | 30 | 21 | 16 | 3.96 |
| 1500 | 6 | 12 | 23 | 36 | 42 | 36 | 24 | 18 | 4.41 |
| 1800 | 7 | 14 | 27 | 42 | 49 | 41 | 27 | 19 | 4.86 |
| 2100 | 8 | 16 | 31 | 49 | 55 | 47 | 30 | 20 | 5.31 |
| 2400 | 9 | 18 | 36 | 55 | 55 | 53 | 33 | 22 | 5.76 |

Type KSD5035 - 425mm Module Insertion (dB) at Octave Band Centre Frequencies (Hz)

| Length (mm) | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | 'K' (Face) |
|-------------|-----------|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| 600 | 5 | 8 | 13 | 18 | 23 | 19 | 15 | 13 | 2.21 |
| 900 | 6 | 10 | 17 | 25 | 29 | 24 | 18 | 15 | 2.55 |
| 1200 | 7 | 12 | 20 | 31 | 36 | 29 | 21 | 16 | 2.89 |
| 1500 | 9 | 14 | 24 | 38 | 42 | 34 | 24 | 18 | 3.23 |
| 1800 | 10 | 16 | 28 | 45 | 49 | 39 | 27 | 20 | 3.57 |
| 2100 | 11 | 18 | 31 | 51 | 55 | 44 | 30 | 21 | 3.91 |
| 2400 | 12 | 20 | 35 | 55 | 55 | 49 | 33 | 23 | 4.25 |

Type KSD5040 - 450mm Module Insertion (dB) at Octave Band Centre Frequencies (Hz)

| Length (mm) | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | 'K' (Face) |
|-------------|-----------|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| 600 | 5 | 7 | 12 | 16 | 19 | 15 | 13 | 12 | 1.61 |
| 900 | 6 | 9 | 15 | 22 | 26 | 20 | 15 | 13 | 1.87 |
| 1200 | 7 | 11 | 19 | 28 | 32 | 24 | 17 | 14 | 2.12 |
| 1500 | 8 | 13 | 22 | 34 | 39 | 29 | 20 | 16 | 2.38 |
| 1800 | 9 | 15 | 26 | 40 | 46 | 33 | 22 | 17 | 2.63 |
| 2100 | 10 | 17 | 29 | 46 | 52 | 38 | 24 | 19 | 2.89 |
| 2400 | 11 | 19 | 33 | 52 | 55 | 43 | 27 | 20 | 3.14 |

Type KSD5045 - 475mm Module Insertion (dB) at Octave Band Centre Frequencies (Hz)

| Length (mm) | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | 'K' (Face) |
|-------------|-----------|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| 600 | 5 | 6 | 10 | 14 | 16 | 13 | 11 | 11 | 1.23 |
| 900 | 6 | 8 | 13 | 19 | 22 | 16 | 12 | 12 | 1.43 |
| 1200 | 7 | 10 | 17 | 24 | 28 | 20 | 14 | 13 | 1.64 |
| 1500 | 8 | 12 | 20 | 29 | 34 | 24 | 16 | 14 | 1.85 |
| 1800 | 9 | 13 | 24 | 34 | 41 | 28 | 18 | 15 | 2.06 |
| 2100 | 10 | 15 | 27 | 39 | 47 | 32 | 20 | 16 | 2.27 |
| 2400 | 11 | 17 | 31 | 45 | 53 | 36 | 22 | 18 | 2.47 |


Type KSD5050 - 500mm Module Insertion (dB) at Octave Band Centre Frequencies (Hz)

| Length (mm) | <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> | 'K' (Face) |
|-------------|-----------|------------|------------|------------|-------------|-------------|-------------|-------------|------------|
| 600 | 4 | 5 | 8 | 12 | 12 | 10 | 9 | 9 | 0.92 |
| 900 | 5 | 7 | 11 | 16 | 18 | 13 | 10 | 10 | 1.09 |
| 1200 | 6 | 9 | 14 | 21 | 24 | 16 | 12 | 11 | 1.26 |
| 1500 | 7 | 10 | 18 | 25 | 29 | 19 | 14 | 12 | 1.43 |
| 1800 | 8 | 12 | 21 | 29 | 35 | 22 | 15 | 13 | 1.60 |
| 2100 | 9 | 14 | 25 | 33 | 41 | 25 | 17 | 14 | 1.77 |
| 2400 | 10 | 16 | 28 | 38 | 47 | 28 | 19 | 15 | 1.94 |

MELINEX

When Melinex linings are used the following allowances should be made to the Insertion Loss

| <u>63</u> | <u>125</u> | <u>250</u> | <u>500</u> | <u>1000</u> | <u>2000</u> | <u>4000</u> | <u>8000</u> |
|-----------|------------|------------|------------|-------------|-------------|-------------|-------------|
| x 1 | x 1 | x 0.95 | x 0.85 | x 0.8 | x 0.65 | x 0.55 | x 0.5 |



TYPICAL SPECIFICATION

Type **KSD50** Series Attenuator.

| | |
|------------------|--|
| Manufacturer: | Conabeare Acoustics Limited - 0118 930 3650 |
| Attenuator Type: | KSD50 Series Rectangular Attenuator. |
| Outer Skin: | Pre-Galvanised Steel Sheet Outer Skin throughout. |
| Splitters: | 45kg/m ³ density mineral wool retained behind glass fibre tissue and expanded or perforated metal having a minimum of 30% free area. |
| Flanges: | Generally Mez20, Mez30 or Mez40 Flanges although other flange systems/types are available. |
| Finish: | Mill Finish as Standard. |
| Description: | Fabricated Steel Attenuator comprising pre-galvanised steel components throughout. Attenuator to be factory assembled using mechanical fixings and supplied in one section for incorporation into the works. |

AVAILABLE OPTIONS

- MX - Melinex Lining to Splitters.
- HS - Horizontal Splitters.
- SP - Special Construction such as Double Skinned.
- CRP - Chlorinated Rubber Paint.
- HT - High Temperature.
- XT - Cross Talk Attenuator.
- VB or HB - Bend Attenuator - Contact Our Engineering department for Advice.
- Stainless Steel Fabrication.
- PVC Fabrication.

PRESSURE LOSS

To establish the pressure loss through the attenuator based on air on and off condition being straight length of duct as detailed within BS EN ISO 7535:2003. The following example should be used;

Example

KSD5020 Attenuator at 1.4 metres wide x .9 metres high x 1.5 metres long having a duty of 4m³/s

Step 1 - Module size = 0.35m x number of modules = 4 (1.4/0.35) x height = .9m which = (0.35 x 4 x .9) = 1.26

Step 2 - (Airflow (m³/s) / step 1) squared = (4 m³/s / 1.26)² = 3.17² = 10.08

Step 3 - (step 2 x 'K' Factor) x 0.6 = (10.08 x 10.47) x 0.6 = Pressure drop of 63Pa

CONABEARE ACOUSTICS LIMITED

11 Chiltern Enterprise Centre, Station Road, Theale, Berkshire. RG7 4AA.



Telephone [0118 930 3650](tel:01189303650)



sales@conabeare.co.uk



Facsimile [0118 930 3912](tel:01189303912)



www.conabeare.co.uk